










Craig Wire Products Magnet Wire Cross Reference Guide

CWP Part Number	Thermal Class	Insulation Type	NEMA Standard (MW1000)	Application Type	
CW Formvar	105°C	Formvar	MW 15 (Round) MW 18 (Sq/Rect)	<ul style="list-style-type: none"> • Oil Fill Transformers • Coils • Motors 	
CWDPG CW Enamel/SPG <i>*Unvarnished Enamel/SPG ^{UL}</i> <i>Varnish options available</i>	155°C	Polyester Glass Fiber	MW 45 (Round) MW 46 (Sq/Rect)	<ul style="list-style-type: none"> • AC/DC Motors • Generators • Field Coils 	
CW MICA	155°C	Mica tape		<ul style="list-style-type: none"> • High Voltage Motors • Wind Machines • Transit Motors 	
CW200 ^{UL} CW200Quad ^{UL} CW200PLUS ^{UL}	200°C	Polyester with Polyamide-imide Overcoat	MW 35-C (Round) MW 36-C (Sq/Rect)	<ul style="list-style-type: none"> • AC/DC Motors • Generators • Hermetic Motors • Transformers • Electric Vehicles 	

^{UL} UL certified product



Craig Wire Products Magnet Wire Cross Reference Guide

CWP Part Number	Thermal Class	Insulation Type	NEMA Standard (MW1000)	Application Type	
CW Nomex®	220°C	Aromatic Polyamide Paper	MW 60-C	<ul style="list-style-type: none"> • Dry Type Transformers • Form Wound Coils 	
CW ML ^{UL} (HML, QML, SML) <i>Varnish options available</i>	240°C	Aromatic Polyimide Enamel	MW 16-C (Round) MW 20-C (Sq/Rect)	<ul style="list-style-type: none"> • Aerospace • Traction Motors • Field Coils • Synchronous Motors 	
CW240TP	240°C	Aromatic Polyimide Tape	MW 65-C (Round) MW 64-C (Sq/Rect)	<ul style="list-style-type: none"> • AC/DC Motors • Submersible Pumps • Aerospace • Traction Motors • Electric Vehicles 	

^{UL} UL certified product